

## CORRIGENDUM - I

TENDER REF.NO. CUSB/PSD/G.House/TENDER/26/2018-19, Dated :- 01/03/2019

"Furniture in proposed Guest house Building and multipurpose hall of CUSB at Panchanpur, Gaya (Bihar)"

### Queries with Clarifications:-

S. N	Relevant Clause No. & Page No.	Queries of Tenderer	Clarifications by the University
1.	Item sl. 7, 29.1, 29.2 & 38 of BOQ At page No. 25 of 44, 34 of 44 & 35 of 44	Kindly Provide detailed description of item No. 29.1, 29.2 and item No.38	"Technical Specification" of item No. 7, 29.1, 29.2 & 38 along with Bill of Quantity is being uploaded as Annexure- A-1/1 on website. Tenderers to follow the same.
	Clause No. 10.3 of General Conditions of Purchase at page No. 12 of 44	Completion time of supply and installation is 60 days which appears to be very less as Seasoning time of timber itself shall be minimum 30 days. Kindly increase completion time to 90 days.	Completion time of the subject work has been extended to 90 days from the date of issuance of order.
2.	Clause No. 10.3 at page No. 12 of 44	In your above refereed tender the time given for delivery and installation is 60 days. In this regard we would request you to kindly extend the delivery period to 120 days as sourcing and drying of wood takes a lot of time and the required wood size in not always readily available in the market.	Completion time of the subject work has been extended to 90 days from the date of issuance of order.
3.	Item No. 7 of Technical Specification at page No. 25 of 44	Item Serial No. 7 - Side Table Custom Made : In this item the picture and item description does not correlate. Kindly clarify.	"Technical Specification" of item No. 7, 29.1, 29.2 & 38 along with Bill of Quantity is being uploaded as Annexure- A-1/1 on website. Tenderers to follow the same.
	Item No. 29.1 of Technical Specification & Bill of Quantity at page No. 28 of 44 & 34 of 44	Item Serial No.29.1 – Wardrobe a) In this item required back ply thickness is 6mm. The back ply thickness should be 9 mm. b) Wardrobe shelves are taken in 12 mm thick plywood. Here the thickness should be 18 mm. c) Quantity of drawers to be provided in the wardrobe is not mentioned.	"Technical Specification" of item No. 7, 29.1, 29.2 & 38 along with Bill of Quantity is being uploaded as Annexure- A-1/1 on website. Tenderers to follow the same.

Page 1 of 23


S. N	Relevant Clause No. & Page No.	Queries of Tenderer	Clarifications by the University
	Item No. 29.2 of Technical Specification at page No. 28 of 44	<p>Item Serial No.29.2 – Wardrobe</p> <p>a) In this item required back ply thickness is 6 mm. The back ply thickness should be 9 mm.</p> <p>b) Wardrobe shelves are taken in 12 mm thick plywood. Here the thickness should be 18 mm.</p> <p>c) Quantity of drawers to be provided in the wardrobe is not mentioned.</p> <p>d) Wardrobe front/shutters have been taken in Veneer pasting and wardrobe side panels have been taken in 1 mm laminate pasting. Both front/shutter and side panels should be same i.e. either veneer pasting or laminate pasting.</p>	<p>“Technical Specification” of item No. 7, 29.1, 29.2 &amp; 38 along with Bill of Quantity is being uploaded as Annexure- A-1/1 on website. Tenderers to follow the same.</p>
	Item No. 29.2 of Bill of Quantity at page No. 34 of 44	Item Serial No.29.2 - Wall Paneling: In this item details of wood/plywood grid on wall below the veneer panel has not been mentioned. Kindly Clarify.	<p>“Technical Specification” of item No. 7, 29.1, 29.2 &amp; 38 along with Bill of Quantity is being uploaded as Annexure- A-1/1 on website. Tenderers to follow the same.</p>
	Clause No. 14 (EMD) at page No. 6 of 44	Exemption to NSIC units regarding EMD, will be consider or not.	Shall be considered as per rule of the GOI.
	Clause No. 3.a Physical at page No. 3 of 44	In your Eligibility criteria point 3(a) “Similar Works is defined as Supply & Installation of “Wooden Furniture”, Please clarify Modular Kitchen and other modular furniture will be consider instead of wooden furniture or not.	No change. It will remain as per Tender.
4.	Clause No. 5 at page No. 4 of 44	In Point 5 - You have mentioned about IS specification code and CPWD specification. But you have already given your specification and also furniture are to supply custom make. Please clarify in which items we should follow IS Codes & CPWD specification.	All materials used in the scope should confirm relevant IS codes and CPWD specifications unless and otherwise exclusively specified.
	Clause No. 9.ii.h (Technical Bid Document) at page No. 5 of 44	SL. No. 9.ii.h – Catalogue item must be shown on website, but we have not our website. Will our tender got rejected in absence of website? Please clarify.	No tender shall be rejected in absence of website. Tenderer should submit the desired documents as per tender conditions.

S. N.	Relevant Clause No. & Page No.	Queries of Tenderer	Clarifications by the University
	New Clause	New Clause being introduced as Clause No. 32 of General Condition of Purchase	<p>In event of ambiguity in details of the scope, follow order of precedence shall follow:-</p> <ol style="list-style-type: none"> <li>1. Bill of Quantity</li> <li>2. Technical Specification</li> <li>3. Drawings &amp; Sketches</li> <li>4. CPWD specification &amp; IS Codes</li> <li>5. Manufacturer's specification</li> <li>6. Conditions of contract</li> <li>7. Purchase rules and Procedures of the University available on website "cusb.ac.in"</li> </ol>

CENTRAL UNIVERSITY OF SOUTH BIHAR, GAYA  
CORRIDENDUM -1

Annexure-A 1/1, Technical Specification  
**Tender Notice No & Date: CUSB/PSD/G.House/TENDER/26/2018-19, Dated 01/03/2019**  
NAME OF JOB: Supply & fixing of Furniture in proposed Guest House Building and multipurpose hall of CUSB at Panchanpur, Gaya (Bihar)

Note: Tenderer to submit this revised annexure- A1/1 duly sealed and signed along with the technical bid in addition to all pages of tender document.

Item Sl.	Room	Item Name	Technical Specification	Product image/ Reference
7.	Entrance lobby & 2nd floor lounge Area	Side table _Custom made table	Supplying and fixing Side Table of size 550x550x550mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. Top, Legs, Shelf & supporting structure made up of red sheesham wood. Top 01 no. (550x550x28mm), legs 04 nos. (410x75x75mm), shelf 01 nos. (530x530x18mm), top support horizontal frame panel 04 nos. (50mmx28mm), shelf support horizontal frame panel 04 nos. (30mmx28mm). Mortise and Tenon joints on legs and frame panels to be provided. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per direction of Officer In-charge.	
29.1	VIP suit living room, Single Bed Room & dormitory	Wardrobe	Providing and fixing wooden Wardrobe up to 24" deep made up of 18mm thick marine (B.W.R) ply on all sides with 9mm thick ply for rear. Including Shutters with designer Laminates of minimum two designs or more of minimum 1mm thick. The back of door shutter shall be of 1mm white Laminate. Note: For Shutters only block board with pine wood shall be used for doors of Wardrobe. Shelves to be provided are of 18mm thick commercial ply as per approved	Please refer Sketch No. 1/29 & 2/29

29.2	VIP suit living room	Wardrobe	<p>drawing. The wardrobe shall have 02 nos. of drawers. All internal surfaces are to be laminated with 1.0 mm thick lamination sheet of approved make and colour and external sides to be laminated with 1mm lamination sheet of approved make and colour with wooden beadings for the edges as per the instructions of the officer in charge including providing all necessary Hardware such as brass hinges, MS Heavy duty powder coated telescopic channels, 20mm dia. SS rail for cloth hangers, tower bolts, locks, magnetic locks, handles, rollers etc. complete as per direction of Officer-in-charge (Measurement of front elevation shall be considered for making payment).</p>	
			<p>Providing and fixing wooden Wardrobe up to 24" deep made up of 18mm thick marine (B.W.R) ply on all sides with 9mm thick ply for rear. Including Shutters and side panels with teak/ sheesham veneer of minimum 0.45 mm thick pasted with ply board, the Back of door shutter shall be of 1 mm thick laminate of matching shade all including 3 coats of melamine polishing on veneer to a matching shade. Note: For Shutters only block board with pine wood shall be used for doors of Wardrobe. Shelves to be provided are of 18mm thick commercial ply as per approved drawing. The wardrobe shall have 02 nos. of drawers. All internal surfaces are to be laminated with 1.0 mm thick lamination sheet of approved make and colour and wardrobe side panels to be in teak/ sheesham veneer of minimum 0.45 mm thick pasted on ply board with wooden beadings for the edges as per the instructions of the officer in charge including providing all necessary Hardware such as brass hinges, MS Heavy duty powder coated telescopic channels, 20mm dia. SS rail for cloth hangers, tower bolts, locks, magnetic locks, handles, rollers etc. complete as per direction of officer-in-charge (Measurement of front elevation shall be considered for making payment).</p>	Please refer Sketch No. 1/29 & 2/29
38	VIP SUIT,	WALL	Providing wall panelling using 12mm thick marine ply with 0.45	Standard plain wall panelling with

	LIVING AREA, CONFERENCE ROOM, DINING HALL AND WAITING AREA	PANNELIN G	mm thick Teak/ sheesham veneer pasted with adhesive including 3 coats of melamine polish, all allied hardware, beadings, making grooves, side leaping and 50mm x 12 mm thick BWR grade plywood grid on wall as approved by officer-in-Charge. Note: Shop drawings to be got approved prior to procurement planning.	leaping at edge and moulded beading
--	--	------------	---	-------------------------------------

CENTRAL UNIVERSITY OF SOUTH BIHAR, GAYA  
CORRIDENDUM -1

(Price bid proforma); To be placed in envelope -C' after filling details and duly sealed and signed as per tender conditions

Bill of Quantity

**Tender Notice No & Date: CUSB/PSD/G.House/TENDER/26/2018-19, Dated 01/03/2019**

NAME OF JOB: Supply & fixing of Furniture in proposed Guest House Building and multipurpose hall of CUSB at Panchanpur, Gaya (Bihar)

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
1	VIP suit living room & VIP Lounge	SOFA 1 SEATE R CUSTO M MADE	Supplying and Fixing 1 seater sofa of following specifications. Overall dimensions will be 850Lengthx800 Widthx900 Height. Seating Area Length- 600mm. Clear Seating Area Width- 500mm. Seating Area Height from Ground- 450mm. Arm rest Height from Ground-630mm. Stitching shall be done by Nylon thread. INNER frame work material shall be hardwood Babool having moisture content less than 14%. Thickness of Plywood used shall be 12mm. Standard of Plywood used shall be Standard : IS 303 Commercial Plywood. SEAT FOAM Thickness (mm) shall be 125mm which is a mixture as 25mm 32 Density Superfoam + 100mm 32 Density. IT shall be Slabstock foam. Armrest & backrest shall have 50mm thick 32 density foam . The sofa shall have 01 nos. loose back cushion having thickness 100mm (550x450x100mm) which is a mixture as 25mm 32 Density Superfoam + 75mm 32 Density foam. Exposed wooden base/legs of sofa shall be hardwood Red Sheesham containing sapwood not more than 10% and having moisture content not more than 14%. Sofa base shall be made out of 38mm thick wood having overall dimensions 730Lx700Wx150H finished with 03 coats of Satin Melamine Polish. The sofa base shall have 4 legs of 38x38x150mm and 4 wooden frames 38x38mm thick connecting all 4 legs. Fixing of base shall be done by Self Tapping screws. Type of Glue used shall be rubber. The sofa seat shall have 03 nos. of S- Springs running across front to back and 04 nos. of elastic band (niwar) running across the length. Sofa to be covered with good quality fabric/leatherette of approved shade. All complete as per drawing & direction of Officer In-charge.	10	each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
2	VIP suit living room & VIP Lounge	SOFA 3 SEATE R CUSTO M MADE	Supplying and Fixing 3 seater sofa of following specifications. Overall dimensions will be 1900Lengthx800 Widthx900 Height. Seating Area Length- 1650mm. Clear Seating Area Width- 500mm. Seating Area Height from Ground- 450mm. Arm rest Height from Ground-630mm. STITCHING shall be done by Nylon thread. INNER frame work material shall be hardwood Babool having moisture content less than 14%. Thickness of Plywood used shall be 12mm. Standard of Plywood used shall be Standard : IS 303 Commercial Plywood. SEAT FOAM Thickness (mm) shall be 125mm which is a mixture as 25mm 32 Density Supersoft + 100mm 32 Density. IT shall be Slabstock foam. Armrest & backrest shall have 50mm thick 32 density foam . The sofa shall have 03 nos. loose back cushion having thickness 100mm (550x450x100mm) which is a mixture as 25mm 32 Density Supersoft foam + 75mm 32 Density foam. Exposed wooden base/legs of sofa shall be hardwood Red Sheesham containing sapwood not more than 10% and having moisture content not more than 14%. Sofa base shall be made out of 38mm thick wood having overall dimensions 1780Lx700Wx150H finished with 03 coats of Satin Melamine Polish. The sofa base shall have 4 legs of 38x38x150mm and 4 wooden frames 38x38mm thick connecting all 4 legs. Fixing of base shall be done by Self Tapping screws. Type of Glue used shall be rubber. The sofa seat shall have 08 nos. of S- Springs running across front to back and 04 nos. of elastic band (niwar) running across the length. Sofa to be covered with good quality fabric/leatherette of approved shade. All complete as per drawing & direction of Officer In-charge.	5	each		
3	VIP lounge & VIP living room	Centre table _Custo m made table	Supplying and fixing Centre Table of size 1000x600x450mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. Top, Legs, Shelf & supporting structure made up of red sheesham wood. Top 01 no. (1000x600x28mm), legs 04 nos. (410x75x75mm), shelf 01 nos. (980x580x18mm), top support horizontal frame panel 04 nos. (50mmx28mm), shelf support horizontal frame panel 04 nos. (30mmx28mm). Mortise and Tenon joints on leg and frame panels. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per direction of Officer In-charge.	5	each		



S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
4	VIP lounge & VIP Suit living room	Side table _Custum made table	Supplying and Fixing Side Table of size 550x550x550mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. Top, Legs, Shelf & supporting structure made up of red sheesham wood. Top 01 no. (550x550x28mm), legs 04 nos. (410x75x75mm), shelf 01 nos. (530x530x18mm), top support horizontal frame panel 04 nos. (50mmx28mm), shelf support horizontal frame panel 04 nos. (30mmx28mm). Mortise and Tenon joints on leg and frame panels. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per direction of Officer In-charge. Pls Change as corrected in RED	6	each		
5	Entrance Lobby/ Second floor lounge	3 SEATE R SOFA CUSTO M MADE	Supplying and Fixing 3 seater sofa of following specifications. Overall dimensions will be 1900 Lengthx700 Widthx880 Height. Seating Area Length- 1650mm. Clear Seating Area Width- 500mm. Seating Area Height from Ground- 450mm. Armrest height 610mm, Backrest height 880mm from floor. Stitching shall be done by Nylon thread. INNER frame work material shall be hardwood Babool having moisture content less than 14%. Thickness of Plywood used (mm) shall be 12mm. Standard of Plywood used shall be Standard : IS 303 Commercial Plywood. SEAT FOAM Thickness (mm) shall be 125mm which is a mixture as 25mm 32 Density Supersoft + 100mm 32 Density. It shall be Slabstock foam. ARMREST FOAM & Backrest foam shall be 50mm thick 32 density foam. The sofa backrest shall have 75mm thick foam which is a mixture as 25mm 32 Density Supersoft + 50mm 32 Density. Exposed wooden base/legs of sofa shall be of hardwood Red Sheesham containing sapwood not more than 10% and having moisture content not more than 14%. Sofa base shall be made out of 38mm wood having overall dimensions 1800Lx700Wx170H finished with 03 coats of Satin Melamine Polish. The sofa base shall have 4 legs of 50x50x150mm and 4 wooden frames 60x18mm thick connecting all 4 legs. Fixing of base shall be done by Self Tapping screws. Type of Glue used shall be rubber. The sofa seat shall have 10 nos. of S- Springs running across front to back and 04 nos. of elastic band (niwar) running across the length. Sofa to be covered with good quality fabric/leatherette of approved shade. All complete as per drawing & direction of Officer In-charge. Pls Change as corrected in RED	5	each		
6	Entrance lobby & 2nd Floor lounge Area	Centre table _Custum made table	Supplying and FIXing Centre Table of size 1000x600x450mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. Top, Legs, Shelf & supporting structure made up of red sheesham wood. Top 01 no. (1000x600x28mm), legs 04 nos. (410x75x75mm), shelf 01 nos. (980x580x18mm), top support horizontal frame panel 04 nos. (50mmx28mm), shelf support horizontal frame panel 04 nos. (30mmx28mm). Mortise and Tenon joints on leg and frame panels. 3 coats of Satin Melamine	5	each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
			polish to be done in approved shade. All complete as per direction of Officer In-charge.				
7	Entrance lobby & 2nd floor lounge Area	Side table - Custom made table	Supplying and fixing Side Table of size 550x550x550mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. Top, Legs, Shelf & supporting structure made up of red sheesham wood. Top 01 no. (550x550x28mm), legs 04 nos. (410x75x75mm), shelf 01 nos. (530x530x18mm), top support horizontal frame panel 04 nos. (50mmx28mm), shelf support horizontal frame panel 04 nos. (30mmx28mm). Mortise and Tenon joints on leg and frame panels. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per direction of Officer In-charge.	5	each		
8	Office	Table	Supplying and fixing in position Table of the following specifications. Table size shall be 1650 Width mm x 900 Depth mm x 740 Height mm. Table top shall be 25 mm thick plain particle board (PPB) Clad with 0.6 mm thick post formed laminate and 1 mm thick backing laminate (bdl) .Flat edge Duly sealed with 2 mm thick PVC beading.The modesty shall be 18 mm thick plain particle board (PPB) Clad with 1.0 mm thick decorative laminate (DL) on both sides. Edge Sealed with 2 mm thick PVC beading. Supplying and placing in position ERU of the following specifications. ERU size shall be 1050 Width x 450 Depth x 705 Height. The top of ERU shall be 25 mm thick plain particle board (PPB) Clad with 0.6 mm thick post formed laminate and 1 mm thick Backing Laminate ( BDL).Flat Edge duly sealed with 2 mm thick PVC beading. The Modesty shall be 18 mm thick plain particle board (PPB) Clad with 1.0 mm thick Decorative Laminate (DL) on both sides. Edge sealed with 2 mm thick PVC Beading. Supplying and placing in position HDU of the following specifications. HDU size shall be 1280 Width x 425 Depth x 705 Height.	1	each		
9	Office & reception area	Fabric Office Executive Revolving Chair	Providing and fixing Office Executive Revolving Chair (Blue) (W)-55cm, (H)-60.0cm & size of seat shall be (W)-51.0cm x (D)-49.0cm. Adjustable Seat Height, Locking Mechanism, Armrest, Swivel, Model Number : 802 Cushion PP, Style: Contemporary & Modern, Frame Material Subtype : PVC, Upholstery Material : Fabric, Upholstery Included : Yes, Upholstery Type : Cushion, Chair Features : Adjustable Seat Height, Locking Mechanism, Armrest, Swivel, Finish Type : High Quality Chair with seat height adjustment, Push back with lock facility, whether resistant PP arms, Cushioned seat and mesh back. Care Instructions: "Gently clean using a damp sponge or soft, lint-free cloth on a regular basis. Use a vacuum cleaner service tool to clean the seams. Keep away metal parts from water. "Ergonomic : Yes, Dimensions Weight : 11 kg-15 kg., Frame Material: Plastic. The work shall be carried out as per the instructions and guidance received from Officer in charge.	3	each		

page 10 of 23

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
10	Office	Fabric Office Visitor Chair (Blue)	Providing and Fixing Paradise SGF-2070 Fabric Office Visitor Chair (Blue) Armrest, W x H: 54 mm x 84 mm (2 in x 3 in), Frame Material : Plastic, Upholstery Type : Cushion, Visitor Chair Frame : MS Powder coated Arms : PU, Upholstery : Fabric, Style : Contemporary & Modern, Suitable For : Study & Home Office, Frame Material Subtype : PVC, Upholstery Material : Fabric, Upholstery Included : Yes, Upholstery Type : Cushion, Chair Features : Armrest, Finish Type : Frame : MS powder coated Arms: PU Upholstery : Fabric, Care Instructions : Gently clean using a damp sponge or soft, lint-free cloth on a regular basis. Use a vacuum cleaner service tool to clean the seams. Keep away metal parts from water. Bush Included : No, Bend Direction : Outward, Ergonomic : Yes, Origin of Manufacture : INDIA, Accessories Included : Frame : MS powder coated Arms : PU Upholstery : Fabric, Other Features : High Quality, Long Lasting, Comfortable Chair	2	each		
11	Bed Room VIP Suit	BED Custom made	Supplying and fixing In place of Four Poster Bed of size 1988.8x2121x2100mm to accommodate mattress sized 72"x78" made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. The bed shall have 04 no. legs (70x70x2100mm), side rails 38mm thick 02 nos. (223x38mm), headboard panels 28mm thick 01 no. (100x28mm) & 01 no. (777x28mm), footboard panels 28mm thick 01 no. (100x28mm) & 01 no. (270x28mm), mosquito net rail 04 nos. (50x28mm), wooden support under mattress 1 no. (100x38mm) & 4 nos. (75x28mm). Mattress plywood 12mm thick BWR grade 02 nos. (36x78 inch). The bed shall have 28x20mm wooden battens along all inner surface of headboard/footboard/side rails to support the mattress plywood. The bed headboard /footboard/side rails/plywood supports shall be assembled together with heavy duty M.S. Bed Clamps (dub set) i.e. 06 nos. double bolt bed clamp size 63x38x63mm and 08 nos. single bolt bed clamp size 63x38x38mm fixed with good quality S.S. Screws of 25mm length. All joints to be mortise and Tenon joints. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per drawing & direction of Officer in-charge.	3	each		
12	Bed Room VIP Suit	Mattress custom made	Supplying and fixing King Size Mattress size of 72"x78"x6" , constructed using Bonded Foam With combination of HR Foam covered with Premium knitted Fabric. The mattress shall have a combination of 100mm Thick 90 Density Bonded Foam + 50mm thick 32 Density H.R. foam. Both outer sides shall have knitted fabric covering with quilting of 12mm thick 28 Density foam.	3	each		
13	Bed Room VIP Suit	Standard and King	Supplying and Fixing Standard Size Goose Down and Feather Pillows (17" x 27"), Best Down pillows are filled with the soft, interior plumage of ducks or geese; they also contain coarser outer feathers for extra padding. Our pick for the Best Down/Feather Pillow is the Luxe Pillow,	6	each		

Seal & Signature of Tenderer

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
		sizes Pillow with Pillow Cover	which features three internal chambers: a central chamber containing waterfowl feathers and two outer chambers with white goose down fill. The pillow is constructed with a 300TC cotton cover and a down and feather insert, which can be removed when the cover needs to be washed. Both the cover and the insert have piped edges to secure the fill and prevent materials from escaping.				
14	Single Bed Room	White Pillow Highloft	Supplying and fixing Standard White Pillow Highloft size 18" x 27" (45cm x 67.5cm) This classic hollow fibre pillow has been specially designed to be light and fluffy. It is ideal for people who like their pillow to be high and lofty. This great value pillow features a premium cotton top fabric with a non-allergenic hollow fiber polyester filling. Casing: 100% Fine Indian Cotton, Filling: 100% Polyester Hollowfiber, Height: High, Softness: Medium	70	each		
15	Bed Room VIP Suit	Custom made	Supplying and FIXing of Bedside Cabinet with 03 Drawers of size 550Lx400Wx600Hmm made out of Second Class Teak Wood having moisture content not more than 14%. The cabinet shall have 03 nos. of drawers for storage running on ball bearing telescopic channels. Cabinet Top in 18mm thick wood (550x400x18mm), legs 04 nos. (50x50mm thick), top (front/side/back) horizontal frame panels 04 nos. (38x28mm), front bottom/partition frame panels 03 nos. (28x28mm), cabinet side panels 02 nos. in 18mm thick wood (484x300x18), cabinet back panel in 12mm thick BWR plywood. Each drawer unit shall have 18mm thick front panel 01 no. in wood (450x132.6x18mm), side/back panel 03 nos. in 18mm thick BWR plywood and drawer base panel 01no. in 12mm thick BWR plywood. All joints to be mortise and Tenon joints. With all necessary hardware i.e. good quality 03 nos. 14" telescopic channels and 03 nos. drawer pull handles as approved. 3 coats of Satin Melamine polish to be done in approved shade all around and top shall be of 1 mm thick laminate. All complete as per drawing & direction of Officer In-charge.	6	each		
16	VIP SUITE/ STUDY TABLE	Custom made study table	Supplying and FIXing in place Study Table with 02 Drawers of size 1000x600x750mm made out of Second Class Teak Wood having moisture content not more than 14%. The study table shall have 02 nos. of drawers for storage running on ball bearing telescopic channels. Study Table top in 18mm thick plywood (1000x600x18mm) with teak wood beading on all edges and 1 mm laminate pasting with good quality adhesive "Fevicol S.R." or equivalent, Legs 04 nos. (50x50mm thick), top front horizontal frame panels 01 no. (60x28mm), Side panels 02 nos. in 18mm thick wood (440x238x18mm). It shall have 03nos. leg support frame panel i.e. 01 no. in 28mm thick wood (40x28mm) connecting both back legs and 01 nos. connecting both front & back legs on each side. Each drawer unit shall have 18mm thick front panel 01 no. in wood (280x110x18mm), side/back panels 03 nos. in 18mm thick BWR plywood and drawer base panel 01 no. in 12mm	3	each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
17	Single Bed Room & VIP SUITE/ Dormitar Y-1	CUSTOM MADE STUDY CHAIR	<p>thick BWR plywood. Drawer compartment back shall be made in 12mm thick BWR plywood (280x220mm) and drawer compartment side shall be made in 18mm thick wood. All joints to be mortise and Tenon joints. With all necessary hardware i.e. good quality 02 nos. 18" telescopic channels and 02 nos. drawer pull handles as approved. 3 coats of Satin Melamine polish to be done in approved shade all around and top shall be of 1 mm thick laminate. All complete as per drawing &amp; direction of Officer In-charge.</p> <p>Supplying and fixing of Chair 450x500x1000 mm made out of Second Class Teak Wood having moisture content not more than 14%. Chair front legs 02 nos. (50x50mm), back legs 02 nos. (40x35mm) tapered at an angle of 95 degree from the seat wood panel. Seat bottom frame panel front/back/side 04 nos. in 28mm thick wood (60x28mm). Side Leg support panels 02 nos. in 28mm thick wood (30x28mm). Chair back shall have top/middle panels in 30mm thick wood i.e. 01no. (30x30mm) &amp; 02 nos. (40x30mm). Seat shall have 50mm thick 32 density foam pasted on 12mm BWR plywood covered with good quality fabric/Rexene. Front side of back rest shall have 8mm thick BWR plywood with 25mm thick 32 density foam pasting covered with fabric/Rexene and back side of back rest shall have 6mm thick BWR plywood with 12mm thick 28 density foam pasting covered with fabric/Rexene. Foam to be pasted with good quality adhesive "Fevicol S.R." or equivalent. Good quality fabric/Rexene in approved shade to be used. All joints to be mortise and Tenon joints. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per drawing &amp; direction of Officer In-charge.</p>	36	each		
18	Dining Hall - table	TABEL CUSTOM MADE	<p>Supplying &amp; fixing in position Dining Table of size 1370 x 900 x 750 mm. Top made with 16-18mm thick Black Garenite with 30mm moulding around and properly fixed main frame by adseive and screw. . Table Legs , frames, and support shall be made in Second Class Teak Wood. Legs 90x90mm, Side Horizontal Frames 90x38mm and 03 nos. of support 60x28mm under the top. With all necessary hardware for knock-down and assembly. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per drawing &amp; direction of Officer In-charge.</p>	9	each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
19	Dining Hall - CHAIR	CUSTOM MADE	Supplying and Fixing of Chair 450x500x1000 mm made out of Second Class Teak Wood having moisture content not more than 14%. Chair front legs 02 nos. (50x50mm), back legs 02 nos. (40x35mm) tapered at an angle of 95 degree from the seat wood panel. Seat bottom frame panel front/back/side 04 nos. in 28mm thick wood (60x28mm). Side Leg support panels 02 nos. in 28mm thick wood (30x28mm). Chair back shall have top/middle panels in 30mm thick wood i.e. 01no. (30x30mm) & 02 nos. (40x30mm). Seat shall have 50mm thick 32 density foam pasted on 12mm BWR plywood covered with good quality fabric/Rexene. Front side of back rest shall have 8mm thick BWR plywood with 25mm thick 32 density foam pasting covered with fabric/Rexene and back side of back rest shall have 6mm thick BWR plywood with 12mm thick 28 density foam pasting covered with fabric/Rexene. Foam to be pasted with good quality adhesive "Fevicol S.R." or equivalent. Good quality fabric/Rexene in approved shade to be used. All joints to be mortise and Tenon joints. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per drawing & direction of Officer In-charge.	36	each		
20	Conference Room -Table	CUSTOM MADE TABLE	Supply and Fixing of 22 seater horse-shoe shaped conference table provided with veneered top, back, front & sides pasted over block board. Minimum seating space for 2 person should not be less than 1380(W) X 750(D) X 750(H)mm. Top :- 750mm wide top made out of 38mm (19mm + 19mm) thick commercial board (Century/Green Lam) covered with 4 mm thick cedar wood veneered plywood with wood beading on all edges. Double raceway with Pelmet for wiring purpose with flip top opening to access cable trays below containing wires in matching veneer finish. Full height vertical front/ back/sides made out of 18mm thick commercial board Century/Green-Lam covered with 4 mm thick cedar wood veneered plywood in approved pattern making decorative modesty panel. All complete as per drawing & direction of Officer In-charge.	1	of 22 seater		
21	Conference Room -Chair	Conference Revolving Chair	Supply and fixing Conference Revolving Chair. The seat shall be made up of 1.2+/-0.1cm thick hot pressed plywood and upholstered with fabric or synthetic leather and moulded polyurethane foam. The back shall be made up 1.2+/-0.1cm thick hot pressed plywood upholstered with replaceable fabric or synthetic leather upholstery covers and moulded polyurethane foam. The moulded polyurethane foam shall be of density 45+/-2kg/m <sup>3</sup> , and hardness load 16+/-2kgf for 25% compression. The dimensions of seat shall be- 51.0cm(W) x 48.0cm(D) and of back shall be 48.0cm(W) x 64.5cm(H). The armrest top shall be made of moulded polyurethane and mounted on to a fixed type M.S tubular armrest support chrome plated. The Arm support has static	30	each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
22	Storage - Reception & office	Storgae unit	<p>vertical adjustment of +/-1.5+/-0.05cm. The mechanism of the chair shall have following features : 360° revolving type, Front pivot synchro mechanism, Tilt tension adjustment, Single point control, 4 position locking with anti-shock feature, Seat/Back tilting ratio of 1:2. The backrest shall consist of a fixed type mechanism i.e no back up/down adjustment. The chair shall be provided with pneumatic height adjustment which shall have stroke of 9.0 +/- 0.3 cm. The pedestal shall be fabricated from 0.2+/-0.02cm thick HR sheet, chrome plated and assembled with injection moulded black polypropylene hub cap. The size of the pedestal shall be 66.0+/- 0.5 cm pitch-centre-dia. (76.0 +/- 1.0 cm with castors). The twin wheel castors shall be made black nylon. Overall dimensions of Chair shall be, Width of Chair - 76.0cm, Depth of Chair - 76.0cm as measured from pedestal below. Height from ground - min 91.0 to max 100.0cm. Seat height - min 46.0 to max 55.0cm. Dimensions tolerance / variations shall be within +/- 1 cm. All complete as per drawing &amp; direction of Officer in-charge.</p> <p>Supplying and Placing Big Almirah which shall be of an overall size of 916mm(W)x486mm(D)x1980mm(H) with welded construction. It should have the shelf thickness of 0.7 mm, Back thickness of 0.8mm, Door thickness of 0.8mm (high yield strength) and all other components shall have a thickness of 0.9mm. These components shall be made of CRCA 'D' grade high yield strength. The Almirah should have a Mazak handle and Three way locking mechanism with Shooting Bolts. It should have a height wise adjustable shelf mounting which shall have a Uniformly Distributed Load Capacity of max 40 Kg. It should also have a M10 Screw type Leveller with Hex plastic base. The finishing shall include Epoxy powder coated to the thickness of 50 microns (+/- 10). Plenty of colour options and shelving options shall be available.</p>	3	each		
23	Single Bed Room & VIP suit living room	Coiffe chair - Custom made	<p>Supplying &amp; Placing in position Coffee Chair made up of Second class teak Wood. Overall Size of chair shall be 650 Width x700 Depth x Height 900mm. Front legs 50x28mm, back legs 45x28mm, arm rest 70x28mm, Seat bottom frames (front/side/back) 80x28mm &amp; back top horizontal curved frame 110x28mm in wood. Clear seating Area Length- 550mm. Clear Seating Area depth- 550mm. Seating Height from Ground- 460mm. Arm rest Height from Ground-690mm. STITCHING shall be done by Nylon thread. SEAT FOAM Thickness (mm) shall be 125mm which is a mixture as 25mm 32 Density Supersoft + 100mm 32 Density. It shall be Slabstock foam. Armrest inner side shall be 8mm plywood pasted with 25mm thick 32 density foam and armrest outer side shall be 6mm plywood pasted with 12mm thick 32 density foam, both covered with fabric/leatherette. Backrest inner side shall be 8mm plywood pasted with 75mm thick 32 density foam (which is a mixture of 25mm 32 Density Supersoft + 50mm 32 Density foam) and backrest</p>	70	each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
			outer side shall be 6mm plywood pasted with 12mm thick 32 density foam, both covered with fabric/leatherette. Standard of Plywood used shall be Standard : IS 303 Commercial Plywood. The chair seat shall have 03 nos. of S- Springs running across front to back and 03 nos. of elastic band (niwar) running across the length. Chair to be covered with good quality fabric/leatherette of approved shade. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per drawing & direction of Officer In-charge.				
24	Single Bed Room	Coffee Centre Table - Custom made	Supplying and Fixing Coffee Centre Table of size 700 mm dia. x 450mm height made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. Top, Legs & supporting structure made up of red sheesham wood. Top 700 dia. x 28mm thick, legs 04 nos. (80mm dia x 422mm height with turning ), top support horizontal frame panel 04 nos. (80mmx28mm curved ), Mortise and Tenon joints on leg and frame panels. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per Drawing & direction of Officer In-charge.	32	each		
25	VIP suit living room	Coffee Centre Table - Custom made	Supplying and Fixing Coffee Centre Table of size 700 mm dia. x 450mm height made out of Second class Teak wood having moisture content not more than 14%. Top, Legs, Shelf & supporting structure made up of red sheesham wood. Top 01 no. (700 dia. x 28mm thick), shelf 01 no. (600dia x 18mm thick), legs 04 nos. (422mm height x 80x80mm curved), top support horizontal frame panel 04 nos. (80mmx28mm curved ). Mortise and Tenon joints on leg and frame panels. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per Drawing & direction of Officer In-charge.	3	each		
26	Single Bed Room & dormitory	TV Cabine t - custom made	Supplying & Placing in position TV Wall Panel size 1500Length x 1200Height x100Depth mm made out of 18mm BWR grade Block board with 1mm laminate pasting on front & side panels of approved shade. 02 coats of enamel paint on the back/wall side of the panel. It shall have 01 storage shelf of 250mm depth on the bottom with 180mm internal height of storage compartment. Fixing on wall with necessary hardware and providing holes & cut-outs to accommodate switch, socket and wiring internally. All complete as per drawing & direction of Officer In-charge.	33	each		
27	VIP suit living room	TV Cabine t - custom	Supplying & Placing in position TV Wall Panel size 1800 mm Length x 1200 mm Height x100 mm Depth made out of 18mm BWR grade Block board with 1mm laminate pasting on front & side panels of approved shade. 02 coats of enamel paint on the back/wall side of the panel. It shall have 01 storage shelf of 250mm depth on the bottom with 180mm internal height of storage	3	each		



S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
		made	compartment. Fixing on wall with necessary hardware and providing holes & cut-outs to accommodate switch, socket and wiring internally. All complete as per drawing & direction of Officer In-charge.				
28	Dining Hall	Crockery case	Providing and fixing in position for crockery case of made of internal framework, shelves, drawers, layon slides partitions and shutters with 19 mm thick prelaminated block board of BWR Grade, Decorative Type (BWP-DEC) of approved quality or equivalent stamped with IS-1659:2004 (latest Edition) and prelamination should conform to IS-2046:1995 (latest Edition) including piano type hinges (19x25mm), best quality teak wood lipping around the shutter edges, magnetic ball catchers, brass tower bolt, knobs, handles with SS roses 150 mm x 19 mm dia (Ref. Make - Dorset, Dorma, Godrej or equivalent), spirit polishing/ enamel painting on lipping in required shade matching to the laminate etc. complete in all respects inclusive of cost of all labour, materials, tools, tackles etc. as per drawings, specifications and direction of Site Officer (measurement of cupboard shall be taken as front elevation area of shutters only for payment). Vender to submit the Shop Drawing as per side condition.	20	Sqm		
29 .1	VIP suit living room, Single Bed Room & dormitory	Wardrobe	Providing and fixing wooden Wardrobe up to 24" deep made up of 18mm thick marine (B.W.R) ply on all sides with 9mm thick ply for rear. Including Shutters with designer Laminates of minimum two designs or more of minimum 1mm thick. The back of door shutter shall be of 1mm white Laminate. Note: For Shutters only block board with pine wood shall be used for doors of Wardrobe. Shelves to be provided are of 18mm thick commercial ply as per approved drawing. The wardrobe shall have 02 nos. of drawers. All internal surfaces are to be laminated with 1.0 mm thick lamination sheet of approved make and colour and external sides to be laminated with 1mm lamination sheet of approved make and colour with wooden beadings for the edges as per the instructions of the officer in charge including providing all necessary Hardware such as brass hinges, MS Heavy duty powder coated telescopic channels, 20mm dia. SS rail for cloth hangers, tower bolts, locks, magnetic locks, handles, rollers etc. complete as per direction of Officer-in-charge (Measurement of front elevation shall be considered for making payment).	64	Sqm		
29 .2	VIP suit living room	Wardrobe	Providing and fixing wooden Wardrobe up to 24" deep made up of 18mm thick marine (B.W.R) ply on all sides with 9mm thick ply for rear. Including Shutters and side panels with teak/sheesham veneer of minimum 0.45 mm thick pasted with ply board, the Back of door shutter shall be of 1 mm thick laminate of matching shade all including 3 coats of melamine polishing on veneer to a matching shade. Note: For Shutters only block board with pine wood shall be used for doors of Wardrobe. Shelves to be provided are of 18mm thick commercial ply as per approved	22	Sqm		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
			drawing. The wardrobe shall have 02 nos. of drawers. All internal surfaces are to be laminated with 1.0 mm thick lamination sheet of approved make and colour and wardrobe side panels to be in teak/ sheesham veneer of minimum 0.45 mm thick pasted on ply board with wooden beadings for the edges as per the instructions of the officer in charge including providing all necessary Hardware such as brass hinges, MS Heavy duty powder coated telescopic channels, 20mm dia. SS rail for cloth hangers, tower bolts, locks, magnetic locks, handles, rollers etc. complete as per direction of officer-in-charge (Measurement of front elevation shall be considered for making payment).				
30	Single Bed Room & Dormitory	Single bed-custom made	Providing and fixing of Cot of Size 1945 mmx 955 mmx 482 mm (Length x breadth x height) made out of seasoned kiln dry and chemically treated Red Sheesham Wood framing with moisture content as per IS: 287:1993 and permissible sap wood content composite fitted with 18 mm thick Boiling Water Resistant Solid block board on top, edges lipped with 20mm x 50 mm Sheesham wood lipping all around and satine melamine finish polishing all wood surface and 18 BWR Ply wood single coat priming and 2 coat of synthetic enamel paint of reputed make as per relevant IS Code on underside of bed on block board with appropriate fillers to get neat and smooth finish paint as per CPWD's specification and desired thickness and framing with hardware and fixing arrangement as per drawing and sketch enclosed including 10 mm wide groove on periphery of Bed Cot in main panel of Sheesham wood under the leaping. All four side Leg top side & panel member (vertical to horizontal) should be fixed with ISA 45mm x 45mm x 5mm fitted with 19mm SS Screw. All outside 4no. main panel (95mm x 30mm) should be fixed with Bed clamp of SS 50mm/35mmX50X1 mm thick with 19mm SS Screw (Horizontal to horizontal) with 4no. Legs of size 95mmx 95mmx 432 mm as per sketch No. 1/31. All internal members to be fixed with SS 50mm/35mmX50X1 mm fitting 19mm SS Screw) to long panel all periphery leaping to be fixed with with superior quality adhesive compound "Fevicol" or equivalent and SS screw. All complete as per direction of Officer In-charge. Note: Self driving screws shall be considered of adequate size in place of SS screw.	70	Each		
31	Single Bed Room	Single bed size matre ss	Supply and Placing of " Bed Mattress" of Size 75 x 36 x 3 inch a 70-80 density with 2" BIS certified, rubberized coir, Coir Pad with 25% Dry Rubber, Content 23 density 1" PU Foam on top, One side 7 mm thick quilting of density, 18 kilogram/ cubic meter, Poly Rotto fabric of Maroon colour. All complete as per direction of Officer In-charge	70	Each		
32	Dormitory	Head	Supplying and Fixing of Headrest of size 955x450x68mm to be made with 50mm PU foam, 8mm	6	Each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
	Y	Rest-Dormitory - Custom Made	BWR plywood & 18mm BWR Block board panels pasted with 50mm 40 +/- 2 kg/ cubic meter and covered with 1 mm thick good quality Rexine shall be fixed on 18mm BWR block board. 18mm BWR block board shall have 18x10mm second class teak wood leaping with 03 coats of melamine polish on all edges. Foam to be pasted with good quality adhesive "Fevicol S.R." or equivalent. Good quality Rexene all around on front side of head rest with wall side of block board painted with 1 coat of wood primer & 2 coats of Synthetic enamel paint. Head-rest fitting & fixing on wall with good Quality (ISI made) S.S. Screw 3.5mm dia. x 40mm length and suitable hardware. Wooden leaping all around. Board top to be pasted with good quality adhesive "Fevicol" The Head-rest fittings, wall clamp & SS screw to be provided as per Drawing.. Paints to be applied with priming coat after due process of filling and filling with approved fillers to get a neat and smooth finish paint. All complete as per drawing & direction of Officer In-charge				
33	Single Bed Room	Head Rest--- Custom Made	Supplying and Fixing of Headrest of size 2580x450x68mm to be made with 50mm PU foam, 8mm BWR plywood & 18mm BWR Block board panels pasted with 50mm 40 +/- 2 kg/ cubic meter and covered with 1 mm thick good quality Rexine shall be fixed on 18mm BWR block board. 18mm BWR block board shall have 18x10mm second class teak wood leaping with 03 coats of melamine polish on all edges. Foam to be pasted with good quality adhesive "Fevicol S.R." or equivalent. Good quality Rexene all around on front side of head rest with wall side of block board painted with 1 coat of wood primer & 2 coats of Synthetic enamel paint. Head-rest fitting & fixing on wall with good Quality (ISI made) S.S. Screw 3.5mm dia. x 40mm length and suitable hardware. Wooden leaping all around. Board top to be pasted with good quality adhesive "Fevicol" The Head-rest fittings, wall clamp & SS screw to be provided as per Drawing.. Paints to be applied with priming coat after due process of filling and filling with approved fillers to get a neat and smooth finish paint. All complete as per drawing & direction of Officer In-charge	32	Each		
34	Single Bed Room	side table Custom Made	Supplying and Placing Bedside Cabinet with 01 Drawer and open storage. Cabinet Size 450Lx400Wx500H mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. The cabinet shall have 01 no. of drawer for storage running on ball bearing telescopic channels. Cabinet Top with 1mm laminate of approved shade pasted on 18mm BWR grade Block board with 18x10mm beading on all edges (450x400x18mm), legs 04 nos. (38x38mm thick), top (front/side/back) horizontal frame panels 04 nos. (38x28mm), front/back bottom frame panels 02 nos. (38x28mm), cabinet side panels 02 nos. in 18mm thick red sheesham wood (405x324x18mm), cabinet back panel in 12mm thick BWR plywood. Open storage base shall be in 18mm thick wood. The drawer unit shall have	32	Each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
			18mm thick front panel 01 no. in wood (374x130x18mm), drawer side/back panel 03 nos. in 18mm thick BWR plywood and drawer base panel 01 no. in 12mm thick BWR plywood. All joints to be mortise and Tenon joints. With all necessary hardware i.e. good quality 01 no. 14" telescopic channel and 01 no. drawer pull handles as approved. 3 coats of Satin Melamine polish to be done in approved shade all around and top shall be of 1 mm thick laminate. All complete as per drawing & direction of Officer In-charge				
35	Single Bed Room & VIP Suit & diuble bed rooms	Study Table Custom Made	Supplying and Placing Study Table with 01 Drawer. Size 900Lx550Wx750H mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. The study table shall have 01 no. of drawer for storage running on ball bearing telescopic channels. Top (900x550x18mm) with 1mm laminate of approved shade pasted on 18mm BWR grade Block board with 18x10mm beading on all edges, legs 04 nos. (60x28mm thick), top (front/side/back) horizontal frame panels 04 nos. (38x28mm), table side panels 02 nos. in 18mm thick red sheesham wood (544x87x18mm), table back panel in 18mm thick wood. The drawer unit shall have 18mm thick front panel 01 no. in wood (780x85x18mm), drawer side/back panel 03 nos. in 18mm thick BWR plywood and drawer base panel 01 no. in 12mm thick BWR plywood. All joints to be mortise and Tenon joints. With all necessary hardware i.e. good quality 01 no. 14" telescopic channel and 01 no. drawer pull handles as approved. 3 coats of Satin Melamine polish to be done in approved shade all around and top shall be of 1 mm thick laminate. All complete as per drawing & direction of Officer In-charge.	33	Each		
36	CUPBOARD in all rooms	MIRROR custom made	Supplying & Placing in position Mirror With Wooden Frame size 1700x650x28mm made out of Red Sheesham Wood containing sapwood not more than 10% and having moisture content not more than 14%. It shall have 02 nos. 28mm thick vertical wooden panels of size 1700x80x28mm & 02 nos. 28mm thick horizontal wooden panels of size 508x80x28mm. The wood panels shall have 12mm thick rebate to accommodate 4mm thick Mirror + 8mm thick plywood. The wooden frame shall have 4mm thick mirror of good quality and 8mm thick BWR grade plywood backing. Fixing on wall with necessary hardware. All joints to be mortise and Tenon joints. 3 coats of Satin Melamine polish to be done in approved shade. All complete as per drawing & direction of Officer In-charge.	40	Each		
37	ENTRANCE LOBBY	RECEPTION TABLE - CUSTO	Providing Reception table along with Feature Wall. Reception table of size 2.00 M x 1.80 M and height of 750/1050 mm (As per approved Drawing) made of 18 mm thick BWP Grade block board for table top, vertical sides and modesty panel. The table shall have 02 nos. of top i.e. first (600mm wide) at 750mm height and second (250mm wide) at 1050mm height. All outside	1	Each		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
		M MADE	surfaces of board shall be finished with 4mm thick plywood pasted with .45mm veneer of approved shade. All inside surfaces finished with 1.0 mm thick decorative laminate of approved colour. The table shall also have 01 no 450mm wide storage compartment made of 18mm thick marine plywood pasted with 1mm thick laminate inside and outside. The storage compartment shall have 01 no. drawer of depth 125mm on telescopic channel and rest shutter. All exposed edges lipped with teak wood beading. The feature wall shall be 2.00 M wide and height as per site and made with 18mm thick BWP grade block board finished with 4mm thick plywood pasted with .45mm veneer of approved shade. The entire unit to be complete with all accessories such as knobs handles lock and key arrangements of approved quality. All veneered surface and teak wood beadings to be finished with 3 coats of Satin Melamine polish approved shade. All Complete as per Direction Of Officer-in- Charge				
38	SUIT, LOUNGE, CONFEREN CE HALL, RECEPTION , DINING	WALL PANNE LING	Providing wall panelling using 12mm thk marine ply with 0.45 mm thick Teak/ sheesham veneer pasted with adhesive including 3 coats of melamine polish, all allied hardware, beadings, making grooves, side leaping and 50mm x 12 mm thick BWR grade plywood grid on wall as approved by officer-In-Charge. Note: Shop drawings to be got approved prior to procurement planning.	204	Sqm		

S. N.	Room	Item Name	Item Description	Qty	Unit	Rate (INR)	Amount (INR)
39	MULTI PURPOSE HALL	COUSHIONED COMFORT CHAIR WITH DESKLET	<p>Providing fixing Chairs in which the seat assembly should be made of polyurethane foam moulded with Mild Steel tubular frame insert which should be upholstered with fabric. The insert should be tubular frame made of Dia. 1.9+/-0.02cm x 0.16+/- 0.013cm thk MS ERW (Mild Steel, Electric Resistance Welded) round tube with flexible support straps running across the length and width of the frame. The Seat has an auto-tipup feature making it stay in upright position when not in use enabling clear row passage. Approx. Seat Size : 45.5cm (W) x 46.5cm (D). The back assembly should be made of polyurethane foam moulded with Mild Steel tubular frame insert, upholstered with fabric and has aplastic back cover. The insert should be a tubular frame made of Dia. 1.9+/-0.02cm x 0.16+/-0.013cm thk MS ERW (Mild Steel, Electric Resistance Welded) round tube with flexible support straps running across the length and width of the frame. Approx. Back Size : 45.5cm (W) x 70.4cm (H). The High Resilience polyurethane foam should be moulded with density = 45 +/-3 kg/m3. The Chair rests on the ground on two side panel frames fabricated from 0.12+/-0.020cm thk CR Steel sheet which should be clad with fabric upholstery. The side panel frame should be grouted to the floor using 2 nos. of anchors for each panel through 0.3+/-0.05cm thk Hot Rolled Steel. The Synchro-slide mechanism should be designed using heavy duty slides aiding inn relaxed posture. The slider should be connected to back using linkages to achieve synchronous motion between seat &amp; back. The Synchro-slide has an stroke of 60+/-5 mm and should be mounted on the side panel. The armrest should be made up of solid beech wood with clear lacquer coat. The armrest should be fitted with side panel through concealed zinc plated hinge. The desklet should be made of 1.8 +/- 0.05cm thick prelaminated particleboard with in suit injection moulded polypropylene edgig all around. Desklet Top should be mounted on high pressure die-cast aluminium Arm through metal bracket 0.2+/-0.05cm thk.H.R. steel. The assembly should be mounted on side panel through Desklet arm connector made up of Glass filled nylon (PA +30%GF). Desklet Outer Dimension: 20.8+/-0.1cm W x 30.2+/-0.1cm D. Steel components shall be epoxy polyester powder coated (DFT 40-60 microns).</p>	140	each		
				SUB TOTAL (A)			
				GST @ .....		% (B)	
				GRAND TOTAL (A)+(B)			
Total quoted price in Words:.....							

Page 22 of 23

Seal & Sign of Tenderer

Page 23 of 23

Page 17 of 17

Seal & Signature of Tenderer